Assessing the Impact of Laser- Plasma Instabilities, Hot Electron Fluxes and Far from Equilibrium Kinetic States in Burning Plasmas

Bedros Afeyan, PRI
Eddie Dewald, Harry Robey, Nathan
Meezan, Jim Hammer, Oggie Jones, Peter
Amendt, John Heebner LLNL

Kinetic Effects Workshop LLNL, Livermore, CA 4-7-2016





Polymath

Big Picture: Follow (Or Lead) the Hot e⁻s & Do Constrained Optimization, via Learned Compression in Fully Kinetic

Simulations of e⁻s and ions and EM fields


- Try to exploit laser-plasma instabilities to probe non-thermal, non-steady state, non-equilibrium and non-fluid-model-capturable effects in high energy density plasmas.
- Nonlinear optical processes render a plasma kinetic and non-fluid like over fast time scale (sub-ps) and short length scale (10-100 μ m) evolving distribution functions for electrons and (~10 times slower for) ions.
- Need new experiments, new diagnostics, new simulations and new theoretical models coupling imploding shell dynamics to shocked interface physics, ice-gas interface, ablator-ice interface and wall-fill gas interfaces.
- You don't get rid of LPI (as if you could!). You learn about your plasma using LPI. You also control LPI by properly designing laser pulses on the LPI relevant space and time scales (The STUD pulse program).
- New codes must use parsimonious representations of phase space, be adaptive and learn from previous simulations by compressing information to capture essential length, velocity and time scales and constraining nonlinear solvers in fully implicit approaches by such accumulated data. Bootstrap to ever more rapid convergence via variational constraints.

Hohlraums Contain Plasmas at Different Conditions $(n_e, T_e, u, f_e(v))$ in Different locations at Different Times, Made of He, Be, CH, C, Ne, SiO₂, U, Au, ...



NIF has $P_{drive} > 100$ MB, and has achieved $P_{Stag} > 150 - 200$ GB but needs

 $P_{Stag} > 300$ GB to ignite at < 2 MJ.




LEH window thickness 0.5 +/- 0.05 μm A NIF Hohlraum is a Laser-Plasma Instability (LPI) Candy Store

Non of the plasma conditions or interaction modalities that are manifest on the NIF were ever accessed on Nova or Omega.

It's all different and yet
It remains weakly
characterized, weakly
diagnosed, and studied only
in passing.

Adequate Stringent Control of Laser-Plasma Instabilities Is Required to Achieve Indirect or Direct Drive Ignition





- Energy coupling should be > 90% to achieve high enough $T_{\rm rad}$
- Implosion symmetry requires controlled power balance between "inner" and "outer" beams. Soft X-ray flux on equator vs. poles in space and time must be maintained.
- Must have low capsule preheat (T_{hot}, f_{hot})
- Must control SBS, SRS, $2\omega_p$ & filamentation, cross-beam energy transfer (CBET), hot electron and hard X ray (M Band) proliferation.

The Geometry of NIF Quads: Top View, 4 Cones: Inner (Red 23°, Orange 30°) & Outer (Dark 44° & Light Green 50°)

Per Hemisphere







FIG. 1. Left: A schematic of a NIF ignition *Hohlraum* with the approximate dimensions, showing the inner and outer beam cones entering the *Hohlraum* through the two laser entrance holes. Right: The specific angles of the NIF beam quads, which are color coded: inner quads orange ($\theta = 30^{\circ}$) and red $(\theta = 23.5^{\circ})$, outer quads light $(\theta = 50^{\circ})$ and dark green $(\theta = 44.5^{\circ})$, where θ is the polar angle.

Dispersion Relations of Waves Whose Three Wave Couplings Give Rise to Laser Plasma instabilities





$$\omega_{\text{EMW}}^2 = \omega_p^2 + c^2 k_{\text{EMW}}^2$$

$$\omega_p^2 = \omega_p^2 + 3 v^2 k^2$$

$$\omega_{\text{EPW}}^2 = \omega_p^2 + 3 v_{th}^2 k_{\text{EPW}}^2$$

$$\omega_{\text{IAW}} = \mathbf{u} \bullet \mathbf{k}_{\text{IAW}} + c_s k_{\text{IAW}}$$

$$\boldsymbol{\omega}_0 = \boldsymbol{\omega}_1 + \boldsymbol{\omega}_2$$
$$\boldsymbol{k}_0 = \boldsymbol{k}_1 + \boldsymbol{k}_2$$

$$\omega_{\text{EMW}} = \sqrt{1 + \left(511 / T_{e,keV}\right) k_{\text{EMW}}^2}$$

$$\omega_{\rm EPW} = \sqrt{1 + 3 k_{\rm EPW}^2}$$

$$\omega_{\mathrm{IAW}} = \sqrt{\frac{Z \; m_e}{M_I}} \; k_{\mathrm{IAW}}$$
Kinetic Effects Workshop 2016

Kinetic Effects Workshop 2016

Most Prominent LPI Processes Are: SRS, SBS, 2ω_p & Filamentation



Very dangerous Instability for indirect drive ICF. Did in the Shiva Laser at 1 μ m back in the 70's. Almost equal amounts of hot e- generation and Backscattering

$$\boldsymbol{\omega}_0 = \boldsymbol{\omega}_1 + \boldsymbol{\omega}_2$$
$$\mathbf{k}_0 = \mathbf{k}_1 + \mathbf{k}_2$$

Very dangerous Instability for indirect drive. Almost all the energy goes to the scattered light wave. Velocity gradients can potentially tame it.

Very dangerous instability for direct drive. It has the lowest intensity threshold, all the energy goes to coherent high frequency oscillations of the plasma and then perhaps to IAWs but with preheat getting you first.

Breakup of the laser light into dancing filaments. Really a 4 wave process including both Stokes and Anti-Stokes components interacting with a degenerate zero frequency IAW. Related to Self-Focusing in classical NLO.

We Can Make Rough Estimates for the Thresholds for Self-Organization in Continuously Driven LPI:



$$I_{14}^{2\omega_{p}} \geq 1.62 \frac{T_{e,keV}}{L_{n,100\,\mu m} \lambda_{0,0.35\,\mu m}}$$

$$I_{14}^{SBS} \geq 17 \frac{T_{e,keV}}{L_{v,100\,\mu m} \lambda_{0,0.35\,\mu m}} \left[\frac{0.1}{(n/n_{c})} \right]$$

$$I_{14}^{SRS} \geq 120 \frac{T_{e,keV}}{L_{v,100\,\mu m} \lambda_{0,0.35\,\mu m}} \left[\frac{0.1}{(n/n_{c})} \right]$$
SRS (Convective modes)

SRS (Convective modes)

 $2\omega_{\rm p}$ (Absolute modes)

SRS (Convective modes)

$$EMW \longrightarrow EMW + EPW$$


Typical hot spot gain lengths are
$$\sim 4 f^2 \lambda_0 = 90 \mu \text{m for } f/8$$

= 560 $\mu \text{m for } f/20$

At intensities approaching 10^{15} W/cm², as in the peak of NIF pulses, you are well above threshold for all three. SRS mostly in hot spots or blame it on a multitude of beams making common cause.

Maximum Growth Rate Hyperbola Defines Most unstable $2\omega_{pe}$ Modes:





Universal Normalized Growth Rate for $2\omega_p$



$$\overline{\Gamma}^{2\omega_p} = 1 - \overline{\nu}(\overline{\eta}) - \overline{\eta}^2 / 2 - D / |\overline{\eta}|$$

For Seka's Omega parameters:D \sim 0.113 ie D_{thresh}/D \sim 4.8, roughly 5x above threshold. Expect lots of nonlinearity (and will find it!)

$$\overline{\eta} \equiv \widetilde{\beta} \eta \qquad D = \frac{\varepsilon_L \beta}{2 \, \widetilde{v}_0}$$

$$D = 0.3 \frac{T_{keV}}{\left(I_{1.4W/cm^2} \lambda_{o,\mu m}^2\right) \left(L_{1.00\mu m} / \lambda_{o,\mu m}\right)}$$

Γ_{NO LD}

0.2 0.4 0.6 0.8 1.2 1.4
$$\bar{\eta}$$

-0.5

$$\overline{\eta}_{thresh} = \sqrt{\frac{2}{3}} \qquad D_{thresh} = \left(\frac{2}{3}\right)^{3/2}$$

$$\overline{\eta}_{peak} = D^{1/3}$$

$$\overline{\eta}_{min} \approx D \left[1 + \frac{D}{2\left(1 - 3D^2/2\right)}\right]$$

$$\overline{\eta}_{max} \approx \sqrt{2} \left[1 - \frac{D}{2^{3/2}} - \frac{3}{16}D^2\right]$$

Kinetic Effects Workshop 2016

Let's Plug in Some Numbers:



For the most unstable mode (at the peak of the growth rate curve), at threshold, the perpendicular component of the wavevector of the plasmons is given by:

$$\frac{\lambda_{\perp,peak}}{\lambda_0} = \sqrt{\frac{3}{2}} \tilde{\beta} = 3.368 \times \frac{T_{e,keV}}{\sqrt{I_{14W/cm^2}} \lambda_{0,\mu m}}$$


We will affect the growth rate of this mode if the lateral extent of the hot spot is of this order. That condition becomes:

$$f/\# < 1.68 \frac{T_{e,keV}}{\sqrt{I_{14W/cm^2}} \lambda_{0,\mu m}}$$

Polymath Research Inc.

Landau Damping Rate of an EPW in a Maxwellian Plasma for $k\lambda_D > 0.25$ Is Well Approximated By:


$$\frac{v_{epw}}{\omega_p} (n = 2, k\lambda_D > 0.25) \approx -0.23 + 2.2(k\lambda_D) - 6.6(k\lambda_D)^2 + 6.8(k\lambda_D)^3 - 3.9(k\lambda_D)^4 + 0.96(k\lambda_D)^5$$





$$\alpha_e = \left[\frac{3\Gamma(3/n)}{\Gamma(5/n)} \right]^{1/2}$$

$$\frac{v_{epw}}{\omega_p}(n,k\lambda_D < 0.25) \approx -\frac{\pi}{4} \left[\frac{n}{\Gamma(3/n) \alpha_e^3} \right] \frac{1}{\left(k\lambda_D\right)^3} \exp\left[-\frac{1}{\left(\alpha_e k \lambda_D\right)^2} - \left(\frac{3n}{2 \alpha_e^n}\right) \frac{1}{\left(k\lambda_D\right)^{n-2}} \right]$$











Picket hot electrons generation regions and deposition in high-Z capsule surrogate were inferred from hard x-ray Bremmstrahlung imaging of target emission*





Typically picket hot electrons are emitted as a 200 ps burst and are yery low (Ehot ~10J, Thot ~40




To separate picket hots, ICF laser pulse was truncated after the picket

* E. Dewald et al, Phys. Rev. Lett. 2016


Same technique can be applied for the rise of the main pulse (creating large amount of SRS) by adding CH coating to the Capsule surrogate to maintain ICF hydro and LPI conditions






For the peak, capsule has to be replaced by high-Z sphere embedded into imploding ablator (or add High-Z dopant to ablator) to keep

hydro equivalency






150

hv (keV)

100


Polymath Research Inc.

300




Dewald et al., strive to measure hot electrons fraction Deposited in the capsule and their spatial asymmetry






The Standard 4 Shock Temporal Pulse Shape of NIF with STUD Pulses Superposed: $f_{dc\%} = 20$ in the Foot with T_{pulse} fixed and $f_{dc\%} = 50$ in Main Drive with I_{max} Fixed.






Large gaps in the foot (4 to 1) for interlacing cones and quads. T_{Max} fixed 50% duty cycle during the main (twice as long) drive. I_{Max} Fixed.




A Good Design Space for T_{pulse} Fixed STUD Pulses Research Inc. Is 2010-5010 x1, 1:1:1/2 down to 1:1:1/4



Harmony Simulations

VPIC Simulations Demonstrate Strong SRBS Reduction Using STUD Pulses in NL Kinetic Regime






5 Ingredients Are Needed to Execute the STUD Pulse Program on NIF:

- Implement the SPA ACE Design of STUD Pulse Generation with 1-3 ps features lasting for 250 ps per box. Stack four boxes to get 1 ns. Repeat.
- Conduct experiments on Trident and Jupiter to test LPI control concepts via STUD pulses: Use SPA ACE boxes. Develop and field fast diagnostics: OUFTS, etc. Measure df/dv (t).
- Model CBET and SBS with deterministic to random STUD pulses in any Z plasma regime: from weak to strong damping limits and from weak to strong coupling regimes. Include any angle crossing beams: resolve laser wavelengths, 2^{nd} order in space.
- ^a Model laser propagation through NIF architecture with STUD pulses. Have parallel modeling capability of STUD pulse propagation in laser media as well as in plasmas of interest. 3ω and 2ω
- Design targets with lower average power, lower radiation temperature but with higher capsule to case ratio and thinner ablators: more suitable for LPI control. Can this win?



How Might A STUD Pulse Program on NIF Evolve over Time If Not Made into a Priority?





How Can We Measure the e⁻ VDF of a Fast Nonlinearly and Kinetically Evolving Plasma?



- Use Pump-probe near backscatter geometry with a burst of spikes as the pump.
- Measure the transmission or gain of the probe.
- Back out plasma conditions and isolate the e⁻ or ion VDF information via the kinetic Landau damping rate.
- Compare neighboring regions at the same or nearby densities. Back out the extend of large beam nonlinear phenomena by a control burst of weakly nonlinear interactions under our control with small signal gain.
- Design sequences of spikes in successive STUD pulses so as to have unambiguous evidence of what is taking place in a quiet or highly agitated plasma.
- Designing the right STUD pulse sequences based on previous shots and optimizing and automating the procedure is the key.


Extract the ps Time Scale Evolution of the e⁻ VDF v{df(t)/dv} Using STUD Pulses and SRS/SBS



Probe Diag. Beam either a spectrally broadened and then stretched fiber laser, 1 μ m wavelength, ~ 200 psec, ~ μ J, ~ 30 nm FWHM bandwidth. Amplitude Technologies, Imra.


Or a Ti:Sapphire pumped OPA tunable from 1 μ m to 2 μ m and doubled to cover 500 nm to 1 μ m, ~100 μ J, ~ 30 nm FWHM bandwidth. Coherent or Spectra Physics off the shelf.

The probe diag. beam is chirped so as to encode time to frequency at spectrometer: 5 ps / nm




How Does SRS Amplification Evolve in Time with and w/o STUD Pulses?






How Are e⁻ VDF's Modified In the Presence of Highly Nonlinear Kinetic SRS?








How About More Esoteric States? SRS + SKEENS











http://www.intechopen.com/books/references/computational-and-numerical-simulations/stimulated-raman-scattering-with-a-relativistic-vlasov-maxwell-code-cascades-of-nonstationary poplinger interactions

Take Away Points

- New experiments are proposed to follow the hot e's wherever they may roam.
- New diagnostics are proposed to extract the e⁻ and ion distribution functions from localized regions of space and on very fast time scales (using STUD pulses)
- New physics models can tie hot e⁻ intermittent bursts to shocked interfacial physics with new features that affect ablator and fuel symmetry directly, which degrade implosion performance significantly in a myriad of ways.
- It is worth pursuing the consequences of a ns worth's of x 10 kJ of hot electrons above 170 keV bathing the hohlraum, in high foot implosions.
- Once a tenth of these hot e-s are absorbed into the dense fuel in a highly asymmetric M8/M16 way, they will preferentially heat ions nonuniformly and thus burn nonuniformly.
- It is important to set limits on radiation drive asymmetry and hot e⁻ preheat and late time bombardment asymmetry that unmistakably disallow symmetric fusion burn propagation.

Theory of Two Plasmon Decay in Inhomogeneous Multidimensional Nonuniformly Illuminated Plasmas

$$\left| \tilde{\mathbf{v}}_0 \right|^2 = \frac{\left(I_{\text{KE}} + I_{\text{PE}} \right)}{I_{\text{NORM}}}$$

Minimum Pump Strength-Variational Principle (MPSP)

$$L_{\text{KE}} = \frac{1}{4} \left(\overline{d}_{l_2} - d_{l_1} \right)^2 \overline{\nabla}^2 \nabla^2$$

$$L_{\text{PE}} = \overline{\nabla}^2 \nabla^2 V^2$$

$$L_{\text{NORM}} = -\left| u_0(\mathbf{x}) \right|^2 (\hat{\mathbf{u}}_0 \bullet \nabla)^2 \frac{\left(\overline{\nabla}^2 - \nabla^2 \right)^2}{\varepsilon}$$

B. B. Afeyan & E. A. Williams, Phys. Plasmas 4, 3827 (1997)

$$I_j \equiv (\tilde{\Psi}, L_j \Psi)$$

Hidden Under the Rug of the MPS-VP for 2ω_{pe} Are these Definitions



$$\overline{d}_{l_2} = \left(\boldsymbol{\omega}_0 - \boldsymbol{\omega}_1\right)^2 \left(1 - \frac{i v_2}{\boldsymbol{\omega}_0 - \boldsymbol{\omega}_1}\right) - \boldsymbol{\omega}_p^2(\mathbf{x}_0) + \mathbf{v}_E^2 \, \overline{\nabla}^2$$

$$d_{l_1} = \omega_1^2 \left(1 + \frac{i v_1}{\omega_1} \right) - \omega_p^2(\mathbf{x}_0) + v_E^2 \nabla^2$$

$$\overline{\nabla} \equiv \nabla - i \, \mathbf{k}_0$$

$$V \equiv \omega_p^2(\mathbf{x}) - \omega_p^2(\mathbf{x}_0) = \varepsilon_L z$$

$$\tilde{\mathbf{v}}_0 \equiv \left(\frac{\mathbf{v}_0}{c}\right) \boldsymbol{\omega}_p(\mathbf{x}_0) \frac{\sqrt{\varepsilon}}{2}$$

$$v_E^2 \equiv \frac{3v_{th}^2}{c^2}$$

$$\tilde{\beta} \equiv \frac{\sqrt{\varepsilon} \,\mathrm{v}_{\mathrm{E}}^{2}}{\left|\tilde{\mathrm{v}}_{0}\right|} = 2.75 \frac{T_{\mathrm{e,keV}}}{\left(\mathrm{I}_{14\mathrm{W/cm}^{2}}^{1/2} \lambda_{0,\mu n}\right)}$$

$$\varepsilon \equiv 1 - \omega_p^2(\mathbf{x}_0)$$

$$\varepsilon_{L} = \frac{\omega_{p}^{2}(\mathbf{x}_{0})}{\left(\frac{\omega_{0}L}{c}\right)}$$

$$\omega_p^2(\mathbf{x}_0) \approx \frac{1}{4} - v_E^2(k_1^2 + k_2^2) + v_E^4(k_1^2 - k_2^2)^2 / 4$$

$$\frac{1}{4} \left(\overline{d}_{l_2} - d_{l_1} \right)^2 = \left[\Omega - \frac{1}{2} v_E^2 \left(\overline{\nabla}^2 - \nabla^2 \right) \right]^2$$

$$\omega_{1} = \omega_{p}(\mathbf{x}_{0}) + \overline{\omega}$$

$$\omega_2 = (\omega_0 - \omega_1) - \overline{\omega}$$

$$\Omega = \overline{\omega} - v_E^2 \frac{(k_1^2 + k_2^2)}{2} + i \frac{(v_1 + v_2)}{4}$$

$$\Re(\omega_1) = \frac{1}{2} + \Re(\Omega)$$

$$\Im(\omega_1) = \Im(\Omega) - \frac{(v_1 + v_2)}{4}$$

The Growth Rate of the Most Unstable Mode of Research Inc. $2\omega_{pe}$ in an Inhomogeneous Plasma Is:



$$\operatorname{Im}\left[\omega_{EPW}^{2\omega_{pe}}/\omega_{0}\right] = \tilde{\mathbf{v}}_{0}\left[1 + \frac{(v_{1} + v_{2})/\omega_{p}}{8\tilde{\mathbf{v}}_{0}} - \frac{1}{2}\tilde{\boldsymbol{\beta}}^{2}\boldsymbol{\eta}^{2} - \frac{\varepsilon_{L}}{2\tilde{\mathbf{v}}_{0}|\boldsymbol{\eta}|}\right]$$

$$\tilde{\mathbf{v}}_0 = \frac{1}{2} \sqrt{\varepsilon} \left(\frac{\omega_P}{\omega_0} \right) \frac{\mathbf{v}_0}{c} = 1.85 \times 10^{-3} \sqrt{I_{14, W/cm^2} \lambda_{0, \mu m}^2}$$


$$\varepsilon_L = \frac{\omega_p^2 / \omega_0^2}{(\omega_0 L / c)}$$

$$\eta = \frac{ck_{\perp}}{\omega_0}$$

$$\varepsilon_{L} = \frac{\omega_{p}^{2}/\omega_{0}^{2}}{(\omega_{0}L/c)} \qquad \qquad \tilde{\beta} = 12 \frac{\left(v_{th}^{2}/c^{2}\right)}{\left(v_{0}/c\right)} = 2.75 \frac{T_{e,keV}}{\sqrt{I_{14,W/cm^{2}}\lambda_{0,\mu m}^{2}}}$$

$$I_{14,W/cm^2} \ge 0.54 \frac{T_{e,keV}}{L_{n,100\mu m} \lambda_{0,\mu m}} [1 - \overline{v}]^{-3/2}$$

Dewald Experimental Platform Measuring Hot esby their Hard X ray Bremsstrahlung Signatures



Polymath Research Inc.